



12000NIT HIGH BRIGHTNESS AND ENERGY-SAVING LED DISPLAY

NEPTUNE SERIES

Pixel Pitch: 5.7 / 10 mm (Outdoor)

Die-cast aluminum design

Modules bottom case and control box bottom case use die-cast aluminum design, high-efficiency heat dissipation, stability and protective grade.





High Brightness


12000nit high brightness, dedicated visibility of image even under strong direct sunlight.





Thin and lightweight panel

32% thinner cabinet and 40% lighter weight, saving steel structure cost and transportation cost.



Common cathode design

Lower energy consumption, save 100,000 $\$ for 200 square meters in 5 years.



Smooth corner transition

Supports 90° corner design, ideal for naked-eye 3D.



Application











SPECIFICATION						
	NT Pro		NT Pro E		NT Pro H	
LED Type	SMD2727					
Pixel Pitch	5.7mm	10mm	5.7mm	10mm	5.7mm	10mm
Max. Brightness	5,500nit	7,500nit	8,000nit	8,000nit	10,000nit	12,000nit
Cabinet Material	Aluminum					
Cabinet Dimensions(LxWxD)	960*960*92 mm/37.80x37.80x3.62"					
Weight Per Cabinet	29 kg/63.93 lbs					
Gray Scale	16bit					
Refresh Rate	3840Hz	7680Hz	3840Hz	7680Hz	3840Hz	7680Hz
Viewing Angle(H/V)	140°/120°			80°/70°		
IP Rating (Front/Rear)	IP65/IP54					

CREATIVE DISPLAY www.vmxvisual.com



CREATIVE DISPLAY



Shenzhen VisionMax Technology Co., Ltd.

Web: www.vmxvisual.com Tel: +86-755-2324 5562 Email: sales@vmxvisual.com

Address: Building 1B, Jianfa Yuefu Plaza, Fenghuang Street, Guangming District, Shenzhen, Guangdong, China